

- NDAA Compliance (The NDAA-compliant products are well suited for government, defense and a range of projects subject to the NDAA.)
- Powerful IR LEDs (Equipped with 3rd generation dot matrix IR LEDs, quaranteeing excellent image quality, long lifespan and energy efficiency.)
- Advanced Functions (Boasting to support various advanced functions such as HLC, Defog, ROI.)
- 256G (Supporting ultra-large external microSD/SDHC/SDXC card storage up to 256G.)
- Adjustable 3-Axis Bracket (Providing a robust mounting platform for angle adjustments on a 3-axis plane.)
- ► Smart Stream (Bandwidth, storage and bit rate are saved with Smart Stream On, eg, H.265⁺ saves 70%~80% bandwidth that of H.264.)

Al Video Analytics

The Al Camera Series can intelligently filter objects to focus on human and vehicle detection in multiple events such as Region Entrance, Region Exiting, Loitering, Advanced Motion Detection, etc.



120dB Super WDR

Sensor-based WDR technology allows the camera to record greater scene details with true color reproduction even under the extreme back light and high contrast conditions. The ratio that the brightest light signal values divided by the darkest light signal values is up to 120dB.





0.005Lux Ultra Low-light

The starlight camera is able to deliver high detailed color images even in low light environment reaching 0.005Lux(Color) or 0Lux(B/W), and near infrared light environments without any supplementary lighting.



IP67&IK10

Supporting IP67-rated weather proofing and IK10-rated vandal proof which are the leading level of the industry, the camera is well protected against adverse impact to ensure the performance.



AI Weather-proof Mini Bullet Network Camera



| Camera | Model | MS-C2963-PD (2MP) |
|-----------|-----------------------|--|
| | Image Sensor | 1/2.8" Progressive Scan CMOS |
| | Min. Illumination | Color: 0.005Lux@F1.6 |
| | | B/W: OLux with IR on |
| | WDR | 120dB Super WDR |
| | Lens | 4mm/2.8mm/6mm@F1.6 |
| | Mount | M12 |
| | Field of View | H91°/D106°/V50°(4mm) H111°/D128°/V61°(2.8mm) H55°/D63°/V32°(6mm) |
| | Shutter Time | 1/100000s~1s |
| | IR Distance | Up to 50m |
| | Day/Night Mode | Day/Night/Auto/Customize/Schedule |
| | S/N | >55dB |
| Video | Max. Image Resolution | 1920x1080 |
| | Primary Stream | 60Hz: 30fps@(1920x1080, 1280x960, 1280x720, 704x576) 50Hz: 25fps@(1920x1080, 1280x960, 1280x720, 704x576) |
| | Secondary Stream | 60Hz: 30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192) 50Hz: 25fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192) |
| | Tertiary Stream | 60Hz: 30fps@(1280x720, 704x576, 640x480, 640x360, 352x288) 50Hz: 25fps@(1280x720, 704x576, 640x480, 640x360, 352x288) |
| | Video Compression | H.265 ⁺ /H.265(HEVC)/H.264 ⁺ /H.264/MJPEG |
| | Video Bit Rate | 16Kbps~16Mbps(CBR/VBR Adjustable) |
| | Privacy Masking | Up to 4 areas |
| | ROI | Up to 8 areas |
| | Image Setting | Brightness/Contrast/Saturation/Sharpness |
| Interface | Ethernet | 1*RJ45 10M/100M Ethernet Port |
| Network | Network Storage | NAS(Support NFS, SMB/CIFS), ANR |
| | Protocol | IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL |
| i | | |

AI Weather-proof Mini Bullet Network Camera




| Intelligent Analytics | Video Analysis | Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Object Left, Object Removed |
|--------------------------|----------------------|---|
| System | Storage | Support microSD/SDHC/SDXC Card Local Storage, up to 256G |
| | Advanced Function | BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur |
| | SIP/VoIP Support | Yes, Voice & Video-over-IP |
| | Event Trigger | Motion Detection, Network Disconnection, etc. |
| | Event Action | FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc. |
| | System Compatibility | ONVIF Profile G & Q & S & T, API |
| General | Working Temperature | -40°C~60°C |
| | Working Humidity | 0~90%(Non-condensing) |
| | Power Supply | PoE (802.3af) |
| | Power Consumption | 3W MAX 9W MAX (With IR on) |
| | Weather Proof | Up to IP67-rated for Weather-resistant Performance |
| | Housing | Vandal-proof IK10-rated Metal Housing |
| | Weight | 750g |
| | Dimensions | Ф76mmX214.5mm |
| | Warranty | 3/5 Years |


www.milesight.com


AI Weather-proof Mini Bullet Network Camera




Structure Diagrams














Units: mm

Accessories Support

A01 Pole Mount

Weight: 720g Dimensions: 170*51.5*152.6mm



A03 External Corner Bracket

Weight: 900g Dimensions: 170*152.5*76.3mm



A63 Junction Box

Weight: 620g Dimensions: 134*126*40mm



